



Model(s):	CTC EcoPart 425 + CTC EcoLogic, CTC EcoPart i425 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	141 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	24	kW	Seasonal space heating energy efficiency	η_s	137	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	na	kW	T _j = -7 °C	<i>COP_d</i>	na	-
T _j = +2 °C	<i>P_{dh}</i>	27,2	kW	T _j = +2 °C	<i>COP_d</i>	3,08	-
T _j = +7 °C	<i>P_{dh}</i>	22,2	kW	T _j = +7 °C	<i>COP_d</i>	3,45	-
T _j = +12 °C	<i>P_{dh}</i>	23,0	kW	T _j = +12 °C	<i>COP_d</i>	4,14	-
T _j = bivalent temperature	<i>P_{dh}</i>	22,0	kW	T _j = bivalent temperature	<i>COP_d</i>	3,18	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	1,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,005	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items				For air-to-water heat pumps: Rated air flow rate, outdoors			
Capacity control	Fixed					na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger		3,1/1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	8728	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Warm climate and Low temperature

Model(s):	CTC EcoPart 425 + CTC EcoLogic, CTC EcoPart i425 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	184 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	26	kW	Seasonal space heating energy efficiency	η_s	180	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>Pdh</i>	na	kW	T _j = - 7 °C	<i>COPd</i>	na	-
T _j = + 2 °C	<i>Pdh</i>	23,6	kW	T _j = + 2 °C	<i>COPd</i>	4,60	-
T _j = + 7 °C	<i>Pdh</i>	23,8	kW	T _j = + 7 °C	<i>COPd</i>	4,83	-
T _j = + 12 °C	<i>Pdh</i>	24,0	kW	T _j = + 12 °C	<i>COPd</i>	5,11	-
T _j = bivalent temperature	<i>Pdh</i>	23,6	kW	T _j = bivalent temperature	<i>COPd</i>	4,68	-
T _j = operation limit temperature	<i>Pdh</i>	na	kW	T _j = operation limit temperature	<i>COPd</i>	na	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>Pdh</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COPd</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>Cdh</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	1,8	kW
Thermostat-off mode	<i>P_{TO}</i>	0,022	kW	Type of energy input: Electric			
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-			
Sound power level, indoors/outdoors	<i>L_{WA}</i>	50/na	dB	-			
Annual energy consumption	<i>Q_{HE}</i>	7236	kWh	-			

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Average climate and Medium temperature

Model(s):	CTC EcoPart 425 + CTC EcoLogic, CTC EcoPart i425 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	142 %
Equipped with a supplementary heater:	No	Package efficiency class:	A++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	24	kW	Seasonal space heating energy efficiency	η_s	138	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	22,0	kW	T _j = -7 °C	<i>COP_d</i>	3,25	-
T _j = +2 °C	<i>P_{dh}</i>	22,4	kW	T _j = +2 °C	<i>COP_d</i>	3,64	-
T _j = +7 °C	<i>P_{dh}</i>	22,8	kW	T _j = +7 °C	<i>COP_d</i>	4,02	-
T _j = +12 °C	<i>P_{dh}</i>	23,2	kW	T _j = +12 °C	<i>COP_d</i>	4,40	-
T _j = bivalent temperature	<i>P_{dh}</i>	22,0	kW	T _j = bivalent temperature	<i>COP_d</i>	3,25	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	3	kW
Thermostat-off mode	<i>P_{TO}</i>	0,005	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	14168	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Average climate and Low temperature

Model(s):	CTC EcoPart 425 + CTC EcoLogic, CTC EcoPart i425 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	A+++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	186 %
Equipped with a supplementary heater:	No	Package efficiency class:	A+++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	26	kW	Seasonal space heating energy efficiency	η_s	182	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	23,6	kW	T _j = -7 °C	<i>COP_d</i>	4,69	-
T _j = +2 °C	<i>P_{dh}</i>	23,8	kW	T _j = +2 °C	<i>COP_d</i>	4,88	-
T _j = +7 °C	<i>P_{dh}</i>	24,0	kW	T _j = +7 °C	<i>COP_d</i>	5,06	-
T _j = +12 °C	<i>P_{dh}</i>	24,2	kW	T _j = +12 °C	<i>COP_d</i>	5,23	-
T _j = bivalent temperature	<i>P_{dh}</i>	23,6	kW	T _j = bivalent temperature	<i>COP_d</i>	4,69	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	3,2	kW
Thermostat-off mode	<i>P_{TO}</i>	0,022	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	11628	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Model(s):	CTC EcoPart 425 + CTC EcoLogic, CTC EcoPart i425 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	145 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	24	kW	Seasonal space heating energy efficiency	η_s	141	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	22,4	kW	T _j = -7 °C	<i>COP_d</i>	3,56	-
T _j = +2 °C	<i>P_{dh}</i>	22,8	kW	T _j = +2 °C	<i>COP_d</i>	3,94	-
T _j = +7 °C	<i>P_{dh}</i>	23,2	kW	T _j = +7 °C	<i>COP_d</i>	4,29	-
T _j = +12 °C	<i>P_{dh}</i>	23,4	kW	T _j = +12 °C	<i>COP_d</i>	4,54	-
T _j = bivalent temperature	<i>P_{dh}</i>	22,0	kW	T _j = bivalent temperature	<i>COP_d</i>	3,25	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-18	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	2,8	kW
Thermostat-off mode	<i>P_{TO}</i>	0,005	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	16390	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Model(s):	CTC EcoPart 425 + CTC EcoLogic, CTC EcoPart i425 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	189 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	24	kW	Seasonal space heating energy efficiency	η_s	185	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T j			
T j = - 7 °C	<i>Pdh</i>	23,8	kW	T j = - 7 °C	<i>COPd</i>	4,89	-
T j = + 2 °C	<i>Pdh</i>	24,0	kW	T j = + 2 °C	<i>COPd</i>	5,06	-
T j = + 7 °C	<i>Pdh</i>	24,2	kW	T j = + 7 °C	<i>COPd</i>	5,18	-
T j = + 12 °C	<i>Pdh</i>	24,2	kW	T j = + 12 °C	<i>COPd</i>	5,20	-
T j = bivalent temperature	<i>Pdh</i>	23,6	kW	T j = bivalent temperature	<i>COPd</i>	4,66	-
T j = operation limit temperature	<i>Pdh</i>	na	kW	T j = operation limit temperature	<i>COPd</i>	na	-
For air-to-water heat pumps: T j = - 15 °C (if TOL < - 20 °C)	<i>Pdh</i>	na	kW	For air-to-water heat pumps: T j = - 15 °C (if TOL < - 20 °C)	<i>COPd</i>	na	-
Bivalent temperature	<i>T biv</i>	-20	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P cyc</i>	na	kW	Cycling interval efficiency	<i>COPcyc</i>	na	-
Degradation co-efficient	<i>Cdh</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P off</i>	0,018	kW	Rated heat output	<i>P sup</i>	1,4	kW
Thermostat-off mode	<i>P to</i>	0,022	kW	Type of energy input	Electric		
Standby mode	<i>P sb</i>	0,018	kW				
Crankcase heater mode	<i>P ck</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L WA</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,0	m ³ /h
Annual energy consumption	<i>Q HE</i>	12746	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Qelec</i>	na	kWh	Daily fuel consumption	<i>Qfuel</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Model(s):	CTC EcoPart 425 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	123 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	25	kW	Seasonal space heating energy efficiency	η_s	119	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	23,5	kW	T _j = + 2 °C	<i>COP_d</i>	2,79	-
T _j = + 7 °C	<i>P_{dh}</i>	23,8	kW	T _j = + 7 °C	<i>COP_d</i>	3,09	-
T _j = + 12 °C	<i>P_{dh}</i>	24,5	kW	T _j = + 12 °C	<i>COP_d</i>	3,64	-
T _j = bivalent temperature	<i>P_{dh}</i>	23,6	kW	T _j = bivalent temperature	<i>COP_d</i>	2,87	-
T _j = operation limit temperature	<i>P_{dh}</i>	23,5	kW	T _j = operation limit temperature	<i>COP_d</i>	2,79	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	1,9	kW
Thermostat-off mode	<i>P_{TO}</i>	0,117	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	10694	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	101	%
Daily electricity consumption	<i>Q_{elec}</i>	9,750	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2145	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Model(s):	CTC EcoPart 425 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	147 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	29	kW	Seasonal space heating energy efficiency	η_s	143	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	25,1	kW	T _j = + 2 °C	<i>COP_d</i>	4,02	-
T _j = + 7 °C	<i>P_{dh}</i>	25,3	kW	T _j = + 7 °C	<i>COP_d</i>	4,23	-
T _j = + 12 °C	<i>P_{dh}</i>	25,6	kW	T _j = + 12 °C	<i>COP_d</i>	4,45	-
T _j = bivalent temperature	<i>P_{dh}</i>	25,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,14	-
T _j = operation limit temperature	<i>P_{dh}</i>	25,1	kW	T _j = operation limit temperature	<i>COP_d</i>	4,02	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	4	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,94	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	4,4	kW
Thermostat-off mode	<i>P_{TO}</i>	0,354	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	10386	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	101	%
Daily electricity consumption	<i>Q_{elec}</i>	9,750	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2145	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Average climate and Medium temperature

Model(s):	CTC EcoPart 425 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	129 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	25	kW	Seasonal space heating energy efficiency	η_s	125	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	23,7	kW	T _j = -7 °C	<i>COP_d</i>	2,95	-
T _j = +2 °C	<i>P_{dh}</i>	16,3	kW	T _j = +2 °C	<i>COP_d</i>	3,24	-
T _j = +7 °C	<i>P_{dh}</i>	8,0	kW	T _j = +7 °C	<i>COP_d</i>	3,71	-
T _j = +12 °C	<i>P_{dh}</i>	8,1	kW	T _j = +12 °C	<i>COP_d</i>	4,03	-
T _j = bivalent temperature	<i>P_{dh}</i>	23,5	kW	T _j = bivalent temperature	<i>COP_d</i>	2,81	-
T _j = operation limit temperature	<i>P_{dh}</i>	23,5	kW	T _j = operation limit temperature	<i>COP_d</i>	2,81	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-10	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	0,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,025	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	15501	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	101	%
Daily electricity consumption	<i>Q_{elec}</i>	9,750	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2145	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Average climate and Low temperature

Model(s):	CTC EcoPart 425 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	A+ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	153 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	30	kW	Seasonal space heating energy efficiency	η_s	149	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	25,2	kW	T _j = -7 °C	<i>COP_d</i>	4,10	-
T _j = +2 °C	<i>P_{dh}</i>	25,4	kW	T _j = +2 °C	<i>COP_d</i>	4,26	-
T _j = +7 °C	<i>P_{dh}</i>	25,6	kW	T _j = +7 °C	<i>COP_d</i>	4,40	-
T _j = +12 °C	<i>P_{dh}</i>	25,8	kW	T _j = +12 °C	<i>COP_d</i>	4,54	-
T _j = bivalent temperature	<i>P_{dh}</i>	25,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,13	-
T _j = operation limit temperature	<i>P_{dh}</i>	25,1	kW	T _j = operation limit temperature	<i>COP_d</i>	4,02	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-6	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,94	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	4,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,354	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	15661	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	101	%
Daily electricity consumption	<i>Q_{elec}</i>	9,750	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2145	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Model(s):	CTC EcoPart 425 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	126 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	27	kW	Seasonal space heating energy efficiency	η_s	122	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	23,9	kW	T _j = - 7 °C	<i>COP_d</i>	3,18	-
T _j = + 2 °C	<i>P_{dh}</i>	24,3	kW	T _j = + 2 °C	<i>COP_d</i>	3,49	-
T _j = + 7 °C	<i>P_{dh}</i>	24,7	kW	T _j = + 7 °C	<i>COP_d</i>	3,77	-
T _j = + 12 °C	<i>P_{dh}</i>	25,0	kW	T _j = + 12 °C	<i>COP_d</i>	3,98	-
T _j = bivalent temperature	<i>P_{dh}</i>	23,7	kW	T _j = bivalent temperature	<i>COP_d</i>	2,96	-
T _j = operation limit temperature	<i>P_{dh}</i>	23,5	kW	T _j = operation limit temperature	<i>COP_d</i>	2,79	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-17	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	3,8	kW
Thermostat-off mode	<i>P_{TO}</i>	0,117	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	50/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	20723	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	101	%
Daily electricity consumption	<i>Q_{elec}</i>	9,750	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2145	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Model(s):	CTC EcoPart 425 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	153 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	29	kW	Seasonal space heating energy efficiency	η_s	149	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T j			
T j = - 7 °C	<i>Pdh</i>	25,4	kW	T j = - 7 °C	<i>COPd</i>	4,29	-
T j = + 2 °C	<i>Pdh</i>	25,6	kW	T j = + 2 °C	<i>COPd</i>	4,41	-
T j = + 7 °C	<i>Pdh</i>	25,7	kW	T j = + 7 °C	<i>COPd</i>	4,50	-
T j = + 12 °C	<i>Pdh</i>	25,7	kW	T j = + 12 °C	<i>COPd</i>	4,52	-
T j = bivalent temperature	<i>Pdh</i>	25,2	kW	T j = bivalent temperature	<i>COPd</i>	4,15	-
T j = operation limit temperature	<i>Pdh</i>	25,1	kW	T j = operation limit temperature	<i>COPd</i>	4,02	-
For air-to-water heat pumps: T j = - 15 °C (if TOL < - 20 °C)	<i>Pdh</i>	na	kW	For air-to-water heat pumps: T j = - 15 °C (if TOL < - 20 °C)	<i>COPd</i>	4,18	-
Bivalent temperature	<i>T biv</i>	-17	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P cyc</i>	na	kW	Cycling interval efficiency	<i>COPcyc</i>	na	-
Degradation co-efficient	<i>Cdh</i>	0,93	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P off</i>	0,025	kW	Rated heat output	<i>P sup</i>	4,0	kW
Thermostat-off mode	<i>P to</i>	0,354	kW	Type of energy input Electric			
Standby mode	<i>P sb</i>	0,025	kW				
Crankcase heater mode	<i>P ck</i>	0,000	kW				
Other items							
Capacity control	Fixed						
Sound power level, indoors/ outdoors	<i>L WA</i>	50/na	dB	For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Annual energy consumption	<i>Q HE</i>	18242	kWh	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,0	m ³ /h

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	101	%
Daily electricity consumption	<i>Qelec</i>	9,750	kWh	Daily fuel consumption	<i>Qfuel</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2145	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.