



Warm climate and Medium temperature

Model(s):	CTC EcoPart 430 + CTC EcoLogic, CTC EcoPart i430 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	140 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	30	kW	Seasonal space heating energy efficiency	η_s	136	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	27,0	kW	T _j = +2 °C	<i>COP_d</i>	3,11	-
T _j = + 7 °C	<i>P_{dh}</i>	27,6	kW	T _j = +7 °C	<i>COP_d</i>	3,48	-
T _j = + 12 °C	<i>P_{dh}</i>	28,4	kW	T _j = +12 °C	<i>COP_d</i>	4,12	-
T _j = bivalent temperature	<i>P_{dh}</i>	27,0	kW	T _j = bivalent temperature	<i>COP_d</i>	3,21	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	2,2	kW
Thermostat-off mode	<i>P_{TO}</i>	0,032	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items				For air-to-water heat pumps: Rated air flow rate, outdoors			
Capacity control	Fixed					na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger		3,1/2,1	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	10792	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Warm climate and Low temperature

Model(s):	CTC EcoPart 430 + CTC EcoLogic, CTC EcoPart i430 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	174 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	32	kW	Seasonal space heating energy efficiency	η_s	170	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	29,0	kW	T _j = +2 °C	<i>COP_d</i>	4,55	-
T _j = + 7 °C	<i>P_{dh}</i>	29,4	kW	T _j = +7 °C	<i>COP_d</i>	4,76	-
T _j = + 12 °C	<i>P_{dh}</i>	29,6	kW	T _j = +12 °C	<i>COP_d</i>	5,02	-
T _j = bivalent temperature	<i>P_{dh}</i>	29,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,62	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,96	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	2,4	kW
Thermostat-off mode	<i>P_{TO}</i>	0,097	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	9404	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Average climate and Medium temperature

Model(s):	CTC EcoPart 430 + CTC EcoLogic, CTC EcoPart i430 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	141 %
Equipped with a supplementary heater:	No	Package efficiency class:	A++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	32	kW	Seasonal space heating energy efficiency	η_s	137	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	27,2	kW	T _j = -7 °C	<i>COP_d</i>	3,29	-
T _j = +2 °C	<i>P_{dh}</i>	27,8	kW	T _j = +2 °C	<i>COP_d</i>	3,68	-
T _j = +7 °C	<i>P_{dh}</i>	28,4	kW	T _j = +7 °C	<i>COP_d</i>	4,03	-
T _j = +12 °C	<i>P_{dh}</i>	28,8	kW	T _j = +12 °C	<i>COP_d</i>	4,37	-
T _j = bivalent temperature	<i>P_{dh}</i>	27,2	kW	T _j = bivalent temperature	<i>COP_d</i>	3,34	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-6	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	5,4	kW
Thermostat-off mode	<i>P_{TO}</i>	0,032	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/2,1	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	18316	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000

www.ctc.se

181001



Average climate and Low temperature

Model(s):	CTC EcoPart 430 + CTC EcoLogic, CTC EcoPart i430 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	178 %
Equipped with a supplementary heater:	No	Package efficiency class:	A+++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	32	kW	Seasonal space heating energy efficiency	η_s	174	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	29,2	kW	T _j = -7 °C	<i>COP_d</i>	4,64	-
T _j = +2 °C	<i>P_{dh}</i>	29,4	kW	T _j = +2 °C	<i>COP_d</i>	4,81	-
T _j = +7 °C	<i>P_{dh}</i>	29,6	kW	T _j = +7 °C	<i>COP_d</i>	4,97	-
T _j = +12 °C	<i>P_{dh}</i>	29,8	kW	T _j = +12 °C	<i>COP_d</i>	5,13	-
T _j = bivalent temperature	<i>P_{dh}</i>	29,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,64	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,96	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	4,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,097	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	14934	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Cold climate and Medium temperature

Model(s):	CTC EcoPart 430 + CTC EcoLogic, CTC EcoPart i430 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	144 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	30	kW	Seasonal space heating energy efficiency	η_s	140	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	27,6	kW	T _j = -7 °C	<i>COP_d</i>	3,59	-
T _j = +2 °C	<i>P_{dh}</i>	28,2	kW	T _j = +2 °C	<i>COP_d</i>	3,94	-
T _j = +7 °C	<i>P_{dh}</i>	28,6	kW	T _j = +7 °C	<i>COP_d</i>	4,26	-
T _j = +12 °C	<i>P_{dh}</i>	29,0	kW	T _j = +12 °C	<i>COP_d</i>	4,49	-
T _j = bivalent temperature	<i>P_{dh}</i>	27,2	kW	T _j = bivalent temperature	<i>COP_d</i>	3,28	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-18	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	3,4	kW
Thermostat-off mode	<i>P_{TO}</i>	0,032	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/2,1	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	20278	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000

www.ctc.se

181001

Cold climate and Low temperature

Model(s):	CTC EcoPart 430 + CTC EcoLogic, CTC EcoPart i430 PRO		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	180 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	32	kW	Seasonal space heating energy efficiency	η_s	176	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	29,4	kW	T _j = -7 °C	<i>COP_d</i>	4,84	-
T _j = +2 °C	<i>P_{dh}</i>	29,6	kW	T _j = +2 °C	<i>COP_d</i>	4,98	-
T _j = +7 °C	<i>P_{dh}</i>	29,8	kW	T _j = +7 °C	<i>COP_d</i>	5,08	-
T _j = +12 °C	<i>P_{dh}</i>	29,8	kW	T _j = +12 °C	<i>COP_d</i>	5,11	-
T _j = bivalent temperature	<i>P_{dh}</i>	29,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,67	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	na	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-18	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cyh}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyh}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,96	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output	<i>P_{sup}</i>	3,6	kW
Thermostat-off mode	<i>P_{TO}</i>	0,097	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	15539	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000

www.ctc.se

181001



Warm climate and Medium temperature

Model(s):	CTC EcoPart 430 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	124 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	29	kW	Seasonal space heating energy efficiency	η_s	120	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	26,8	kW	T _j = +2 °C	<i>COP_d</i>	2,77	-
T _j = + 7 °C	<i>P_{dh}</i>	27,2	kW	T _j = +7 °C	<i>COP_d</i>	3,09	-
T _j = + 12 °C	<i>P_{dh}</i>	28,0	kW	T _j = +12 °C	<i>COP_d</i>	3,65	-
T _j = bivalent temperature	<i>P_{dh}</i>	26,9	kW	T _j = bivalent temperature	<i>COP_d</i>	2,86	-
T _j = operation limit temperature	<i>P_{dh}</i>	26,8	kW	T _j = operation limit temperature	<i>COP_d</i>	2,77	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	2,2	kW
Thermostat-off mode	<i>P_{TO}</i>	0,119	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/2,1	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	12132	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	100	%
Daily electricity consumption	<i>Q_{elec}</i>	9,851	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2167	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Warm climate and Low temperature

Model(s):	CTC EcoPart 430 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	150 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	31	kW	Seasonal space heating energy efficiency	η_s	146	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	na	kW	T _j = -7 °C	<i>COP_d</i>	na	-
T _j = +2 °C	<i>P_{dh}</i>	28,6	kW	T _j = +2 °C	<i>COP_d</i>	4,03	-
T _j = +7 °C	<i>P_{dh}</i>	28,9	kW	T _j = +7 °C	<i>COP_d</i>	4,22	-
T _j = +12 °C	<i>P_{dh}</i>	29,3	kW	T _j = +12 °C	<i>COP_d</i>	4,45	-
T _j = bivalent temperature	<i>P_{dh}</i>	28,7	kW	T _j = bivalent temperature	<i>COP_d</i>	4,09	-
T _j = operation limit temperature	<i>P_{dh}</i>	28,6	kW	T _j = operation limit temperature	<i>COP_d</i>	4,03	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,94	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	2,3	kW
Thermostat-off mode	<i>P_{TO}</i>	0,357	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	10756	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	100	%
Daily electricity consumption	<i>Q_{elec}</i>	9,851	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2167	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Average climate and Medium temperature

Model(s):	CTC EcoPart 430 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	A+ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	128 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	30	kW	Seasonal space heating energy efficiency	η_s	124	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	27,0	kW	T _j = -7 °C	<i>COP_d</i>	2,93	-
T _j = +2 °C	<i>P_{dh}</i>	16,6	kW	T _j = +2 °C	<i>COP_d</i>	3,24	-
T _j = +7 °C	<i>P_{dh}</i>	11,6	kW	T _j = +7 °C	<i>COP_d</i>	3,63	-
T _j = +12 °C	<i>P_{dh}</i>	11,8	kW	T _j = +12 °C	<i>COP_d</i>	3,94	-
T _j = bivalent temperature	<i>P_{dh}</i>	26,8	kW	T _j = bivalent temperature	<i>COP_d</i>	2,79	-
T _j = operation limit temperature	<i>P_{dh}</i>	26,8	kW	T _j = operation limit temperature	<i>COP_d</i>	2,79	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-10	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	3,2	kW
Thermostat-off mode	<i>P_{TO}</i>	0,025	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/2,1	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	18765	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	100	%
Daily electricity consumption	<i>Q_{elec}</i>	9,851	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2167	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000

www.ctc.se

201106



Average climate and Low temperature

Model(s):	CTC EcoPart 430 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	155 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	34	kW	Seasonal space heating energy efficiency	η_s	151	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	28,70	kW	T _j = -7 °C	<i>COP_d</i>	4,11	-
T _j = +2 °C	<i>P_{dh}</i>	29,0	kW	T _j = +2 °C	<i>COP_d</i>	4,27	-
T _j = +7 °C	<i>P_{dh}</i>	29,2	kW	T _j = +7 °C	<i>COP_d</i>	4,41	-
T _j = +12 °C	<i>P_{dh}</i>	29,5	kW	T _j = +12 °C	<i>COP_d</i>	4,55	-
T _j = bivalent temperature	<i>P_{dh}</i>	28,8	kW	T _j = bivalent temperature	<i>COP_d</i>	4,14	-
T _j = operation limit temperature	<i>P_{dh}</i>	28,6	kW	T _j = operation limit temperature	<i>COP_d</i>	4,03	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-6	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,94	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	5,4	kW
Thermostat-off mode	<i>P_{TO}</i>	0,357	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,8/2,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	17699	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	100	%
Daily electricity consumption	<i>Q_{elec}</i>	9,851	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2167	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Cold climate and Medium temperature

Model(s):	CTC EcoPart 430 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	126 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	31	kW	Seasonal space heating energy efficiency	η_s	122	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	27,30	kW	T _j = -7 °C	<i>COP_d</i>	3,19	-
T _j = +2 °C	<i>P_{dh}</i>	27,8	kW	T _j = +2 °C	<i>COP_d</i>	3,50	-
T _j = +7 °C	<i>P_{dh}</i>	28,2	kW	T _j = +7 °C	<i>COP_d</i>	3,78	-
T _j = +12 °C	<i>P_{dh}</i>	28,6	kW	T _j = +12 °C	<i>COP_d</i>	3,99	-
T _j = bivalent temperature	<i>P_{dh}</i>	27,0	kW	T _j = bivalent temperature	<i>COP_d</i>	2,95	-
T _j = operation limit temperature	<i>P_{dh}</i>	26,8	kW	T _j = operation limit temperature	<i>COP_d</i>	2,77	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	3,00	-
Bivalent temperature	<i>T_{biv}</i>	-17	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	4,3	kW
Thermostat-off mode	<i>P_{TO}</i>	0,119	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	53/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	3,1/2,1	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	23522	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	100	%
Daily electricity consumption	<i>Q_{elec}</i>	9,851	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2167	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

EnerTech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000

www.ctc.se

200701



Cold climate and Low temperature

Model(s):	CTC EcoPart 430 + CTC EcoZenith i555		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	155 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	33	kW	Seasonal space heating energy efficiency	η_s	151	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	29,10	kW	T _j = - 7 °C	<i>COP_d</i>	4,29	-
T _j = + 2 °C	<i>P_{dh}</i>	29,3	kW	T _j = + 2 °C	<i>COP_d</i>	4,42	-
T _j = + 7 °C	<i>P_{dh}</i>	29,4	kW	T _j = + 7 °C	<i>COP_d</i>	4,51	-
T _j = + 12 °C	<i>P_{dh}</i>	29,4	kW	T _j = + 12 °C	<i>COP_d</i>	4,53	-
T _j = bivalent temperature	<i>P_{dh}</i>	28,8	kW	T _j = bivalent temperature	<i>COP_d</i>	4,16	-
T _j = operation limit temperature	<i>P_{dh}</i>	28,6	kW	T _j = operation limit temperature	<i>COP_d</i>	4,03	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	4,19	-
Bivalent temperature	<i>T_{biv}</i>	-17	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,94	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,025	kW	Rated heat output	<i>P_{sup}</i>	4,6	kW
Thermostat-off mode	<i>P_{TO}</i>	0,357	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,025	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-	na	3,8/2,6	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	53/na	dB	-	3,8/2,6		m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	20588	kWh				

For heat pump combination heater:

Declared load profile / Energy efficiency class	XXL / A			Water heating energy efficiency	η_{wh}	100	%
Daily electricity consumption	<i>Q_{elec}</i>	9,851	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	2167	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.